
Legal Description Pre-Approval
APPROVED
All transfers are subject to
Athens County Conveyance Standards

MAY 0 7 2019

Jill Thompson Athens County Auditor





DESCRIPTION OF A 65.444 ACRE TRACT

Situated in Fractions 4 & 12, Section 19, T.6, R.13, Ames Township, Athens County, Ohio and being part of the land as described in Volume 547, Page 2157 and all of the land as described in Volume 554, Page 638, of the Official Records of Athens County, Ohio and being more particularly described as follows:

Commencing at an iron pin called for at the Southeast corner of Fraction 12, thence N 00° 21' 48" W, 1087.35 feet (calculated) to a point in Federal Creek, and also being the **Point of Beginning** for the survey herein described:

Thence along the North line of Jago (516-1524 O.R.),

N 87° 47' 43" W, 1003.59 feet to an iron pin found at the Northeast corner of Poole (399-1160 O.R.), passing an iron pin found at 114.81 feet;

Thence along the North line of Poole and a boundary line agreement (554-2042 O.R.)

N 87° 47' 43" W, 1739.58 feet, to an iron pin set;

Thence continuing along the line of Poole,

N 02° 18' 35" E, 775.36 feet to a point in County Road 35 (Fleming Road), passing an iron pin set at 745.36 feet;

Thence along said road the following eight courses:

- (1) N 61° 45' 04" E, 260.84 feet to a point;
- (2) N 64° 22' 00" E, 338.48 feet to a point;
- (3) N 39° 15' 04" E, 187.26 feet to a point;
- (4) N 19° 10' 53" E, 274.07 feet to a point;
- (5) N 37° 05' 49" E, 78.36 feet to a point;
- (6) N 64° 25' 06" E, 88.47 feet to a point;
- (7) N 89° 01' 56" E, 125.65 feet to a point;
- (8) S 76° 20' 55" E, 89.70 feet to a point;

Thence leaving said road, and along the lines of Kasler (171-30 O.R.),

S 02° 28' 58" W, 487.63 feet to an iron pin previously set, passing an iron pin previously set at 23.12 feet;

S 86° 52' 51" E, 1365.03 feet to a point in Federal Creek, passing an iron pin set at the East edge of an abandoned railroad bed at 1222.37 feet;

Thence along said creek the following five courses:

- (1) S 13° 15' 45" W, 184.13 feet to a point;
- (2) S 19° 55' 22" E, 247.38 feet to a point;
- (3) S 32° 53' 36" E, 243.11 feet to a point;
- (4) S 09° 27' 44" E, 234.75 feet to a point;
- (5) S 17° 37' 06" E, 237.89 feet to the point of beginning and containing 65.444 acres of which 4.316 acres are contained within Fraction 4 and 61.128 acres are contained within Fraction 12;

Subject to all easements and rights of way of record.

Iron pins set are 5/8 inch by 30 inch long rebar w/ plastic I.D. Cap stamped "Branner P.S. 6805"

Bearing: Grid North - N.A.D. 83 - Ohio South Zone

The above description is based on a field survey completed May, 2019 by

Jeb Branner, S.I., E.I., under the supervision of:

John M. Branner P.S. 6805

In my sen



