## **DESCRIPTION OF A 1.175 ACRE TRACT**

The following described tract is in the City of Athens, Farm Lot 48, Section 11, Township 9 North, Range 14 West, Athens Township, Athens County, Ohio. Being part of the Thomas W. Parfitt tract as recorded in Official Record 309 at Page 1835. Being more accurately described as follows.

Beginning at the northwesterly corner of Lot 11 of the Terrace Heights Subdivision, thence South 82°14'44" East, along the northerly line of said Lot11, a distance of 9.05 feet to a point on the westerly right-of-way Columbus Road, thence North 04°47'16" East, along the westerly right-of-way of Columbus Road, a distance of 50.04 feet to an iron pin set, said iron pin being the **TRUE POINT OF BEGINNING** of the herein described tract;

Thence South 67°39'16" West, along the westerly right-of-way of Circle Drive (40' right-of-way), a distance of 45.21 feet to an iron pin set;

Thence South 27°39'16" West, continuing along the westerly right-of-way of Circle Drive (40' right-of-way), a distance of 150.05 feet to an iron pin set;

Thence South 73°40'10" West, through the tract of which this description is a part, a distance of 187.58 feet to an iron pin set;

Thence North 22°07'45" West, a distance of 194.10 feet to a 5/8" rebar with i.d. cap stamped "L.F. Swoyer, P.L.S. 6765" found at the southwesterly corner of the Deddens Development, Ltd. Tract as recorded in Official Record 327, at Page 1373;

Thence North 82°53'32" East, along the southerly line of the said Deddens Development, Ltd. tract, a distance of 123.30 feet to a 5/8" rebar with i.d. cap stamped "L.F. Swoyer, P.L.S. 6765" found;

Thence North 73°40'10" East, continuing along the southerly line of the said Deddens Development, Ltd. tract a distance of 258.07 feet to a 5/8" rebar with i.d. cap stamped "L.F. Swoyer, P.L.S. 6765", found on the westerly right-of-way of Columbus Road;

Thence South 04°47'16" West, along the westerly right-of-way of Columbus Road, a distance of 65.00 feet to the true point of beginning, containing 1.175 acres.

Being more particularly described and delineated on a 8 1/2" by 14" plat (drawing #04054A01) attached hereto and made a part hereof. This description is valid only if the plat is attached and recorded with the description as a complete document in its original form and not retyped or altered in any way.

All iron pins set for this survey are 5/8" rebar (30" long) with i.d. cap set, stamped "Dana Exline 7060."

Bearings are rotated to grid north of the Ohio State Plane Coordinate System, South Zone NAD 83.

Being subject to all legal right-of-ways and easements.

The above description was prepared from deed and survey records.

Description Checked for Mathematical Accuracy Athens County ENGINEER'S OFFICE

BY: S. Blauses

Dana A. Exline

Professional Surveyor #7060

State of Ohio

Date: 7/7/04

ATHAN

