

SOUTHEASTERN LAND SURVEYS

LEONARD F. SWOYER
REGISTERED PROFESSIONAL LAND SURVEYOR

3428 Pleasant Hill Road Athens, Ohio 45701 740/593-8701

Situated in Lease Lot 61, Outlots 91,95 and 96 of Section 15, Town 9, Range 14, Athens Township, Athens City, Athens County, Ohio and described as follows:

Commencing at the northeast corner of said Outlot 91 on the South line of West Union Street; thence along said South line North 84 degrees 44 minutes 00 seconds West, a distance of 90.00 feet to a point, the northwest corner of a 20.34 acre tract described in Volume 277 Page 648 of the Athens County Deed Records and the northeast corner of a 20.6266 acre tract described in Volume 145 Page 639 of the Athens County Official Records; thence along the east line of said 20.6266 acre tract and the west line of the said 20.34 acre tract South 5 degrees 03 minutes 00 seconds West, a distance of 312.98 feet to a set railroad spike, THE TRUE POINT OF BEGINNING; thence continuing South 5 degrees 03 minutes 00 seconds West along said line, a distance of 835.90 feet to a set iron pin the point of curvature of a non-tangent curve, concave to the North, having a radius of 1337.70 feet, a central angle of 9 degrees 34 minutes 18 seconds, and a chord of 223.21 feet bearing North 68 degrees 25 minutes 47 seconds West; thence West along said curve and the south line of the said 20.6266 acre tract, a distance of 223.47 feet to a set iron pin; thence on a new line North 5 degrees 03 minutes 00 seconds East, a distance of 624.56 feet to a set railroad spike; thence North 31 degrees 38 minutes 07 seconds East, a distance of 165.35 feet to a set railroad spike; thence South 84 degrees 57 minutes 00 seconds East, a distance of 140.00 feet to the point of beginning containing 3.8409 acres, and being a part of a 20.6266 acre tract described as parcel one in Volume 145 Page 639 of the Athens County Official Records, there being 2.07 acres out of Outlot 91, 0.79 acres out of Outlot 95, 0.93 acres out of Outlot 96 and 0.0509 acres out of Lease Lot 61.


Note: Unless otherwise noted, all set iron pins are 5/8 inch diameter rebar and 30 inches in length and capped with a plastic identification marker inscribed L.F. Swoyer P.S. 6765. The above description was prepared under the supervision of Leonard F. Swoyer Professional Land Surveyor Number 6765 and was based on a survey performed by Southeastern Land Surveys dated March

21, 2003. Subject to all easements and right of ways of record.

O.

Description checked for Mathematical Accuracy ATHENS COUNTY ENGINEER'S OFFICE

SUBDIVISIONS



8/2 HLH