RE 13 Rev. 12-72

KNOW ALL MEN BY THESE PRESENTS:

| That  |
|---|
| hereinafter referred to as the grantor (as used herein, Grantor includes the  |
| plural and words in the masculine includes the feminine) in consideration of  |
| the sum of Dollars (\$)   |
| to him paid by the State of Ohio, the Grantee, the receipt whereof is hereby  |
| acknowledged, does hereby grant, bargain, sell and convey to the said         |
| Grantee, its successors and assigns forever, the following described real     |
| estate:   |
| Situated in the County of <u>Athens</u> , State of Ohio, and in <u>Athens</u> |
| Township, Section 22, Lot No. 137, Town 9 N, Range 14 W, and                  |
| bounded and described as follows:   |

## PARCEL NO. 14WD

Being a parcel of land lying along the  $\_\underline{left}$  side  $\_$  of the centerline of a survey, made by the Department of Transportation, being located within the following described points in the boundary thereof:

at an iron pin set at the Southeast corner of Lot 137, 44.34 feet left of Station 166+18.09; thence North 03 Degrees 37 Minutes 08 Seconds East along the East line of Lot 137 a distance of 85.40 feet to centerline Station 166+91.08 from the centerline of a survey made in 1993 by the Ohio Department of Transportation of State Route 682 in Lot 137, Section 22, Athens Township, Athens County, Ohio; thence North 27 Degrees 39 Minutes 29 Seconds West along the centerline a distance of 114.40 feet to centerline Station 168+05.48; thence South 62 Degrees 20 Minutes 31 Seconds West with a right angle from the centerline a distance of 12.80 feet to the Grantor's Southeast property corner, 12.80 feet left of Station 168+05.48; said point being the True Place Of Beginning; thence South 64 Degrees 33 Minutes 57 Seconds West along the Grantor's South property line a distance of 37.22 feet to an iron pin set at the Westerly Existing Right-Of-Way line, 50.00 feet left of Station 168+06.92; thence North 21 Degrees 46 Minutes 51 Seconds West a distance of 98.85 feet to an iron pin set, 45.00 feet left of Station 169+00.00; thence North 62 Degrees 12 Minutes 58 Seconds West a distance of 36.94 feet to an iron pin set, 70.00 feet left of Station 174+00.00; thence South 89 Degrees 51 Minutes 02 Seconds West a distance of 36.79 feet to an iron pin set, 104.00 feet left of Station 169+37.00; thence North 00 Degrees 50 Minutes 39 Seconds West a distance of 52.93 feet to an iron pin set at the Grantor's North property line, 91.41 feet left of Station 169+79.50; thence South 89 Degrees 35 Minutes 38 Seconds East along the Grantor's North property line a distance of 60.42 feet to the Grantor's Northeast property corner, 32.99 feet left of Station 169+65.41; thence South 28 Degrees 51 Minutes 11 Seconds East along the Grantor's West property line a distance of 166.04 feet to the Place Of Beginning.

This description is based on a survey made by the Ohio Department of Transportation under the direction and supervision of Franklin D. Blair, Registered Surveyor No. 5676.

It is understood that the strip of land above described contains 0.173 acres, more or less, including the present road which occupies 0.135 acres, more or less.

The above described area of 0.173 acres is to be deleted from Auditor's Parcel No.  $\underline{A04-00200362-00}$  which contains  $\underline{0.780}$  acres.

Description checked for Mathematical Accuracy ATHENS COUNTY ENGINEER'S OFFICE EY: 8-30-90

110