

ROBINSON SURVEYING

MEMBER-PROFESSIONAL LAND SURVEYORS OF OHIO 12355 LIARS CORNER ROAD, MILLFIELD, OHIO 45761

ALAN D. ROBINSON Registered Land Surveyor TELEPHONE (740) 593-8774

DESCRIPTION OF A 1.599 ACRE TRACT

Situated in farm Lot 111, Section 23, Town 9, Range 14, Athens Township, Athens County, Ohio, and being a part of a 7 acre tract (tract two), a part of a 8.61 acre tract (tract one) and the remainder of a 50' x 180' lot (tract three) described in Volume 6, Page 913 Official Records of Athens County more and being particularly described as follows:

Commencing at a found Stone at the Southwest corner of Farm Lot 111;

thence, following a fence line, South 83 degrees 35 minutes 23 seconds East, a distance of 442.28 feet to an iron pin set;

thence, leaving said fence line on a random line, North 7 degrees 29 minutes 11 seconds East, a distance of 132.00 feet to an iron pin set;

thence South 83 degrees 35 minutes 23 seconds East, a distance of 204.46 feet to an iron pin set, said iron pin set being the POINT OF BEGINNING of the following described tract;

thence North 10 degrees 28 minutes 06 seconds West, a distance of 229.34 feet to an iron pin set; thence North 77 degrees 03 minutes 47 seconds East, a distance of 272.28 feet to an iron pin set in the West Right-of-way of State Route 682, passing an iron pin set at 262.54 feet;

thence, following said Right-of-way, South 14 degrees 24 minutes 53 seconds East, a distance of 104.03 feet to a point;

thence South 75 degrees 35 minutes 07 seconds West, a distance of 1.22 feet to an iron pin found; thence South 15 degrees 16 minutes 26 seconds East, a distance of 122.47 feet to an iron pin found at the Northeast corner of a 1.00 acre tract described in Volume 257, Page 209 Athens County Deed Records;

thence, following said tract, South 87 degrees 59 minutes 21 seconds West, a distance of 26.81 feet to an iron pin set;

thence South 49 degrees 02 minutes 19 seconds West, a distance of 60.72 feet to an iron pin set; thence South 63 degrees 40 minutes 53 seconds West, a distance of 91.74 feet to an iron pin set; thence, leaving said 1.00 acre tract, North 83 degrees 35 minutes 23 seconds West, a distance of 126.60 feet to the POINT OF BEGINNING; said described tract containing 1.599 acres (69,670.1528 square feet), 0.208 acres being out of the aforementioned 8.40 acre tract, 1.243 Acres being out of the aforementioned 7 acre tract and 0.148 acres being out of the aforementioned 50' x180' tract.

Bearings were assumed and are used to denote angles only.

Subject to all easements and right-of-way of record.

All iron pins set are 5/8 inch by 30-inch long rebar with a yellow cap stamped Alan Robinson RLS 8049.

Alan D. Robinson P.S. 8049 bases the above Description on a field Survey completed May 1, 2002,

Cland Verbrison

Athon # 25



ROBINSON SURVEYING

MEMBER-PROFESSIONAL LAND SURVEYORS OF OHIO 12355 LIARS CORNER ROAD, MILLFIELD, OHIO 45761

ALAN D. ROBINSON Registered Land Surveyor TELEPHONE (740) 593-8774

DESCRIPTION OF A 1.003 ACRE TRACT

Situated in Farm Lot 111, Section 23, Town 9, Range 14, Athens Township, Athens County, Ohio, and being a part of a 7.21 acre tract described in Volume 6 Page 913 Official Records of Athens County and being more particularly described as follows:

Commencing at a found Stone at the Southwest corner of Farm Lot 111;

thence, following a fence line, South 83 degrees 35 minutes 23 seconds East, a distance of 442.28 feet to an iron pin set, said iron pin set being the POINT OF BEGINNING of the following described tract;

thence, leaving said fence line on a random line, North 7 degrees 29 minutes 11 seconds East, a distance of 132.00 feet to an iron pin set; thence South 83 degrees 35 minutes 23 seconds East, a distance of 331.06 feet to an iron pin set at the Northwest corner of a 1.00 acre tract described in Volume 257 Page 209 Athens County Deed Records;

thence, following said tract, South 7 degrees 29 minutes 11 seconds West, a distance of 132.00 feet to an iron pin set at a fence corner post found;

thence, leaving said 1.00 acre tract following the aforementioned fence line, North 83 degrees 35 minutes 23 seconds West, a distance of 331.06 feet to the POINT OF BEGINNING; said described tract containing 1.003 acres (43,692.0000 square feet) and is to be continuous and contiguous with the aforementioned 1.00 acre tract.

Bearings were assumed and are used to denote angles only.

Subject to all easements and right-of-way of record.

All iron pins set are 5/8 inch by 30-inch long rebar with a yellow cap stamped Alan Robinson RLS 8049.

Alan D. Robinson P.S. 8049 bases the above description on a field Survey completed May 1, 2002,

Alan O Notoman

Description checked for Mathematical Accuracy ATHENS COUNTY

ENGINEER'S OFFICE BY: Kathy Canto hung DATE: 5-1-02 Alan D. O. Alan D. O.

