


C. Thomas Smith Ohio Professional Surveyor No. 6844

P.O. Box 393

Racine, Ohio 45771

740-949-2524

BEING A PART OF THE CITY OF ATHENS, FARM LOT 25, SECTION 4, TOWNSHIP-9, RANGE-14, ATHENS TOWNSHIP, ATHENS COUNTY, STATE OF OHIO.



2012 by,

C. Thomas Smith

No. 6844

Ohió Professional Surveyor

diffication of the state of the Upto Sectional area Successor No. 6.3 d.p. 396798 0.5 Prophes Charles BEING WPART OF WELVILLE FOR A FARM OUT AS GEO TOWN TO WASHING WEIGHT OF OHIO. 10 H (2-T 16 100) COLABO An Calc Corporation OR 49 Fg 240 3.10 sans . (0.64 app. 7. (0.64 app. 14. (1. ) (0.64 app. 14. (1. ) 50 CHEFFEL ita de divili Secondo, 191 mon oriotili, nselici di Albarcolli Committee and Committee of the Committee A-58708 3798.8 8 8 Cight Ci 740,536 P W 38 00 TO 150 days 137 No. 1. je. 161, s. e. e. e. estraeci and are for ins discaminacion el angles mig. (3) 2): political properties and and 2000 to their view places of the control of the cont S.Beeneur . Wwi TANGAN TAN 11-1-12 TEAST STATE TEAST Plat proposed force an acrost survive made and back to some day or consideration of the constant of the consta VC 5105



C. Thomas Smith Ohio Professional Surveyor No. 6844 P.O. Box 393 Racine, Ohio 45771 740-949-2524

Description of survey for Thomas Zano

Being a part of tracts of land transferred to Thomas A. and Susan J. Zano as recorded in Official Records Volume 465 at page 309 Athens County Recorder's Office, Athens County, Ohio, also being a part of the City of Athens, Farm Lot 25, Section 4, Township-9, Range-14, Athens Township, Athens County, State of Ohio and more particularly described as follows;

Beginning at an existing iron pipe being the grantor's northeast corner which bears South 00°29'02" East a distance of 1262.74 feet from the northeast corner of said Section 4, T-9, R-14 and being a point on the east line of said Farm Lot 25;

Thence along the east line of said Farm Lot 25 and the east line of said Section 4 also being the west line of a 10.64 acre tract transferred to James R. McLaren as recorded in Official Records Volume 346 at page 1511 South 00°29'02" East passing thru the corner of said 10.64 acre tract and continuing along the west line of a 3.79 acre tract transferred to Huntington Realty Corporation as recorded in Official records Volume 379 at page 691 going a total distance of 416.34 feet to an existing iron pin being the northeast corner of a 0.82 acre tract transferred to Herbert W. Brown Revocable Living Trust and Daniel W. Dowler as recorded in Official Records Volume 151 at page 687;

Thence leaving the east line of said Section 4 and along the boundary of said 0.82 acre tract the following two courses;

North 87°59'55" West a distance of 130.11 feet to an existing iron pin;

South 00°27'15" East a distance of 275.00 feet to a 5/8" iron pin set on the north right of way line 2. of East State Street;

Thence leaving the boundary of said 0.82 acre tract and along said north right of way line North 87°59'55" West a distance of 50.05 feet to a 5/8" iron pin set being the southeast corner of a 0.851 acre tract transferred to the McDonald's Corporation as recorded in Official Records Volume 385 at page 135;

Thence leaving said north right of way line and along the boundary of said 0.851 acre tract the following two courses;

North 00°27'15" West a distance of 275.00 feet to a 5/8" iron pin set;

2. North 87°59'55" West a distance of 135.00 feet to a 5/8" iron pin set being the northwest corner of said 0.851 acre tract;

Thence leaving the boundary of said 0.851 acre tract and along the east line of a 6.22 acre tract transferred to the Athens Shopping Plaza as record in Official Records Volume 110 at page 398 North 00°28'23" West passing thru the northeast corner of said 6.22 acre tract and continuing along the boundary of an 8.10 acre tract transferred to C.O.A.D., an Ohio Corporation as recorded in Official Records Volume 46 at page 240 a total distance of 416.58 feet to an exist an existing iron pipe;

Thence continuing along the boundary of said 8.10 acre tract South 87°57'17" East a distance of 315.09 feet to the principal point of beginning containing 3.3256 acres more or less subject to all legal easements and rights of way.

Bearings are assumed and are for the determination of angles only.

SMITH

RVEYO

All iron pins set are 5/8"X30" rebar with plastic ID cap stamped "CTS-6844".

The above description was prepared from an actual survey made on the 26th day of October, 2012, by C. Thomas Smith, Ohio Professional Surveyor, No. 6844.

Ohio Professional Surveyor No. 6844

Description Checked for Mathematical Accuracy Athens County

ENGINEER'S OFFICE BY: S. Blauser DATE: [1-1-12