



NE. COR L.L. 14

QUINN
175-622
6.0 AC.

Line	Bearing	Distance
1	N 9°36'08"W	111.79'
2	N 3°41'21"E	109.01'
3	N 8°37'15"E	96.18'
4	N 3°54'15"W	79.68'
5	N 17°00'02"W	75.22'
6	N 50°16'40"E	40.94'
7	N 27°28'48"W	102.51'
8	N 40°23'24"W	67.45'
9	N 54°27'29"W	26.06'
10	N 54°27'28"W	45.66'
11	N 73°19'13"W	89.34'
12	N 66°16'11"E	76.89'
13	N 3°22'20"W	112.14'
14	N 9°48'53"W	104.61'
15	N 70°14'46"E	97.27'
16	N 58°44'55"E	105.88'

M 00°00'00"W
1613.42'

*OK TO TRANSFER
ATHENS CITY-COUNTY HEALTH DEPT.
Michael Cayer, R.S.
2-26-04*

Description Checked for
Mathematical Accuracy
Athens County
ENGINEER'S OFFICE

BY: S. Blausen
DATE: 1-29-04



SCALE 1 INCH = 200 FEET
● = IRON PIN SET
○ = IRON PIN FD.
ASSUMED BEARINGS
TO BE USED TO DENOTE
INTERIOR ANGLE ONLY

**SURVEY OF 3 TRACTS (LOTS 3-5)
IN L.L. 13 AND L.L. 14 SECTION 2 AND 3,
T.9, R.14, ATHENS TOWNSHIP
ATHENS COUNTY, OHIO
SURVEYED NOVEMBER 2003**

BY: John M. Branner
**JOHN M. BRANNER P.S. 6805
12500 N. PEACH RIDGE ROAD
ATHENS, OHIO 45701
(740) 592-5778**

