## Description of 1.000 Ac Tract Situated in Section 1 Town 5 Range 13

Canaan Township Athens County, State of Ohio and being more particularly described as follows:

Commencing at the Northwest corner of Section 1 and the Northeast corner of Section 7; thence S 3° 27'34" W along the west line of Section 1, a distance of 2040.82 feet to a found railroad spike in the center of County Road 24, said spike also being the Grantors Northwest property corner and the point of beginning of the tract herein described. Thence along the center line of CR 24 and also being the Grantors north line the following three bearings and distances. S 50° 16'20"E 8.83 feet to a found railroad spike, thence S 61°40'00"E 148.50 feet to a found railroad spike, thence S 72°54'50E 24.96 feet.

Thence leaving said road S 14°19' 40" W 106.80 feet to a set iron pin, passing a PK nail at 12.10 feet, thence S 3°27'34"W 148.10 feet, thence N 86°32'26"W 145.97 feet to a set iron pin.

Thence along the Grantors west line N 03°27'34"E 326.55 feet to the point of beginning and containing 1.0000 acres.

Subject to all legal highways and easements of record.

The above description is based on a survey by Kenneth E. Highland, Registered Professional Surveyor, No. S-7581 and complete March 2, 1994.

\* To a set iron pin.

Kenneth E. Highland

80 Fayette Street Nelsonville, Ohio 4576

5.7581

KENNETH E. HIGHLAND S-7581 STEEL GO GISTERE STATE

Description checked for Mathematical Accuracy ATHENS COUNTY ENGINEER'S OFFICE

ENGINE 3 13 aug 1

