## **DESCRIPTION OF A 2.383 ACRE TRACT**

County, Ohio and being part of a 66.40 acre tract as described in Volume 373, Page 949 Athens County Deed Records and being more particularly described as follows:

Beginning at a stone found at the North-east corner of Fraction 31; Thence, along the east line of Fraction 31 and the west-line of Mansfield (91-239).

S 5°00'00" W,885.77 feet to a p.k. nail set in County Road 90, passing an iron pin found at 416.50 feet;

Thence, along the existing center-line said road, and new lines created by this survey the following bearings and distances:

N 1°10'21" W, 72.77 feet

N 3°58'04" W, 167.75 feet

N 6°09'10" W, 68.84 feet

N 9°48'41" W, 149.88 feet

N 12°37'32" W, 45.30 feet

N 14°59'10" W, 47.97 feet

N 20°50'48" W,141.90 feet N 26°20'01" W, 44.07 feet

N 30°45'22" W, 42.59 feet

N 36°25'05" W, 52.57 feet

N 43°10'15" W, 44.35 feet

N 49°59'50" W, 44.83 feet

N 58°31'36" W, 46.98 feet

N 64°02'51" W, 45.61 feet

N 70°55'38" W, 51.17 feet to a p.k nail set;

Thence, along the North-line of Fraction 31 ,S 85°20'00" E464.23 feet to the point of beginning and containing 2.383 acres

The above described tract is to be continuous and contiguous with Pearl Scott Tract toto the North (371-563)

Subject to all easements and rights of way of record Bearings are to be used to denote interior angles only

The above description is based on a field survey completed October 2010 by John M. Branner P.S. 6805

John m Bonn

John M. Branner S-6805

> Description Checked for Mathematical Accuracy Athens County ENGINEER'S OFFICE BY: S. Blause

