Description Checked for Mathematical Accuracy Athens County NEER'S OFFICE BY leans

Description of a 41.711 Acre Tract

Situated in Fraction 30 and 31, Section 21, T.5, R.13, Canaan Township, Athens County, Ohio and being a part of the First Tract as described in 407-1771 O.R. and being more particularly described as follows:

Commencing at the South-east corner of Fraction 30, thence, along the south-line of said fraction North 86 degrees 44 minutes 12 seconds West, 946.44 feet to a point on the East-line of the aforementioned First Tract; thence, along the East-line of said tract North 03 degrees 19 minutes 24 seconds East, 50.00 feet to an iron pin set and being the point of beginning for the tract of land herein described:

Thence, along new lines created by this survey

N 86° 31' 15" W , 50.10 feet to an iron pin set;

S 4° 15' 59" W, 196.57 feet to an iron pin set;

S 22° 52' 28" E, 200.78 feet to a point in North Coolville Ridge Rd. passing an iron pin set at 186.65 feet;

Thence, along said road:

S 73° 21' 56" W, 236.96 feet;

S 65° 58' 30" W, 374.75 feet;

S 71° 55' 15" W, 156.62 feet;

S 88° 18' 34" W, 114.60 feet;

Thence, leaving said road and along the lines of Petit (107-685 O.R.) and Lucas

(369-629 O.R., 281-1629 O.R.);

N 3° 13' 23" E, 2096.06 feet to an iron pin set, passing an iron pin found at 2072.29 feet;

S 87° 59' 27" E, 102.96 feet to an iron pin set;

N 3° 13' 23" E, 433.62 feet to an iron pin set;

S 86° 46' 37" E, 681.78 feet to an iron pin set;

S 3° 19' 24" W, 1836.45 feet to the point of beginning and containing 41.711 acres.

Subject to all easements and rights of way of record

All iron pins set are 5/8" by 30" long rebar

Bearings: Grid North, N.A.D. 83

The above description is based on a field survey by John M. Branner P.S. 6805 completed January 2013

Jun mm



