

SOUTHEASTERN LAND SURVEYS

LEONARD F. SWOYER REGISTERED PROFESSIONAL LAND SURVEYOR 3428 Pleasant Hill Road Athens, Ohio 45701 614/593-8701

TRACT 4

Situated in Section 6, Town 5, Range 13, Canaan Township, Athens County, Ohio and described as follows:

Commencing at the southwest corner of said Section 6; thence along the south line of said Section 6 on an assumed bearing South 86 degrees 59 minutes 35 seconds East, a distance of 1649.00 feet to an iron pin* at the grantor's southwest property corner; thence along the south line of the grantor and the north line of a 280.75 acre tract North 68 degrees 21 minutes 55 seconds East, passing set iron pins at 480.50 feet and 897.00 feet, for a total distance of 1392.00 feet to a set iron pin, THE TRUE POINT OF BEGINNING; thence along an arbitrary line North 3 degrees 00 minutes 26 seconds East, passing a set iron pin at 441.92 feet, for a total distance of 454.40 feet to a point in Canaan Township Road 221 on the north line of the grantor; thence along said Canaan Township Road 221 and the north line of the grantor the following seven bearings and distances: 1) North 72 degrees 52 minutes 38 seconds East, a distance of 112.50 feet to a point; thence 2) North 74 degrees 02 minutes 29 seconds East, a distance of 238.65 feet to a point; thence 3) North 78 degrees 20 minutes 22 seconds East, a distance of 73.63 feet to a point; thence 4) North 80 degrees 30 minutes 02 seconds East, a distance of 60.22 feet to a point; thence 5) North 65 degrees 38 minutes 43 seconds East, a distance of 39.25 feet to a point; thence 6) North 42 degrees 53 minutes 14 seconds East, a distance of 72.38 feet to a point; thence 7) North 12 degrees 17 minutes 41 seconds East, a distance of 42.56 feet to a point at the grantor's northeast corner on the west line of a 343.15 acre tract described in Volume 308 Page 833 of the Athens County Deed Records; thence along the east line of the grantor and the west line of said 343.15 acre tract South 2 degrees 00 minutes 28 seconds West, passing a found iron pin at 127.26 feet, for a total distance of 462.26 feet to a found iron pin at the grantor's southeast property corner on the north line of aforesaid 280.75 acre tract; thence along the south line of the grantor and the north line of said 280.75 acre tract South 68 degrees 21 minutes 56 seconds West, a distance of 613.41 feet to the POINT OF BEGINNING and containing 5.400 acres, and being a part of a 20.743 acre tract described in Volume 206 Page 751 of the Athens County Official Deed Records. *denotes calculated location of monument based on previous survey.

Note: Unless otherwise noted, all set iron pins are 5/8 inch diameter rebar and 30 inches in length and capped with a plastic identification marker inscribed L.F. Swoyer R.L.S. 6765.

The above description was prepared under the supervision of Leonard F.

Description checked for Mathematical Accuracy ATHENS COUNTY ENGINEER'S OFFICE BY: Downs 22

7-30-97

SUBDIVISIONS

