

## SOUTHEASTERN LAND SURVEYS

LEONARD F. SWOYER
REGISTERED PROFESSIONAL LAND SURVEYOR

3428 Pleasant Hill Road Athens, Ohio 45701 614/593-8701

Situated in the southwest quarter of Section 7, Town 5, Range 14, Carthage Township, Athens County, Ohio and described as follows:

Commencing at the southwest corner of said Section 7; thence North, a distance of 1488,93 feet to a point; thence East, a distance of 1122.03 feet to a point, the northwest corner of the grantor; thence along the west line of the grantor South 11 degrees 20 minutes 00 seconds West, a distance of 132.00 feet to a found iron pipe at the southwest corner of the grantor; thence along the south line of the grantor South 70 degrees 39 minutes 00 seconds East, a distance of 320.80 feet to a point; thence South 63 degrees 59 minutes 59 seconds East, a distance of 75.78 feet to a set iron pin, THE TRUE POINT OF BEGINNING; thence leaving the south line of the grantor North 20 degrees 56 minutes 22 seconds East, a distance of 116.85 feet to a set iron pin; thence South 64 degrees 08 minutes 57 seconds East (passing a set iron pin at 204.77 feet) for a total distance of 222.77 feet to a point in the center of Carthage Township Road 121; thence along the center of said Carthage Township Road 121 South 52 degrees 20 minutes 42 seconds West, a distance of 15.00 feet to a point; thence South 52 degrees 15 minutes 24 seconds West, a distance of 102.45 feet to a point; thence South 58 degrees 39 minutes 32 seconds West, a distance of 26.82 feet to a point; thence leaving the said Carthage Township Road 121 North 58 degrees 38 minutes 00 seconds West (passing a set iron pin at 18.00 feet) a distance of 116.80 feet to a point; thence North 63 degrees 59 minutes 59 seconds West, a distance of 29.72 feet to the point of beginning and containing 0.5207 acre, and being a part of a 4.05 acre tract described in Volume 41 Page 74 of the Athens County Official Deed Records.

Note: Unless otherwise noted, all set iron pins are 5/8 inch diameter rebar and 30 inches in length and capped with a plastic identification marker inscribed L.F. Swoyer R.L.S. 6765. The above description was prepared under the supervision of Leonard F. Swoyer Professional Land Surveyor Number 6765 and based on a survey performed by Southeastern Land Surveys dated October 23,

1996. Subject to all easements and right of ways of record.

196

CONSTRUCTION

SUBDIVISIONS

CAR#7



## SOUTHEASTERN LAND SURVEYS

LEONARD F. SWOYER
REGISTERED PROFESSIONAL LAND SURVEYOR

<sup>1</sup> 3428 Pleasant Hill Road Athens, Ohio 45701 614/593-8701



JULIAN & NANCY L BOGGS 313-665

• - IRON PIN SET o - IRON PIPE FOUND 89°28'45" E 666.65 TRACT SW. COR 0.5704 ACRE RONALD DILLON - 5c. 41-74 4.05 ACRES TRACT I 0.5207 **ACRE** ELMER LEE JR. PAUL P. SHUTTS & LYNDA L. 48-685 SHUTT\$ 27.7 AC. 357-687 4.20 ACRES

LINE BEARING DISTANCE
LI \$52\*20\*42\*W 15.00\*
L2 \$58\*39\*32\*W 26.82\*
L3 N 63\*59\*59\*W 29.72\*
L4 N 28\*35\*33\*E 27.04\*

Description checked for Architectural Archit

Maria de Cara
Plat of Tract 1 0.52 Ac. & Tract 2 0.57 Ac Scale I"= 100'
Surveyed for Ronald Barber Date Oct. 23 1996
the state of
Subdivision southwest quarter of
County Athens
CorporationCounty_Kenton
num fr.
F Swaver Ir Reg. Prof. Land Surveyor No. 6765
F Swaver.Ir Rea. Prof. Land Surveyor No. 0700

Leonard F. Swoyer Jr. Reg. Prof. Land Surveyor No. 6765