



LINE	BEARING	DISTANCE
L 1	S 39°50'56"E	56.53'
L 2	S 34°59'15"E	100.84'
L 3	S 27°32'57"E	97.96'
L 4	S 23°35'12"E	102.46'
L 5	S 23°35'12"E	63.92'
L 6	N 15°52'23"W	104.35'
L 7	S 12°47'03"W	83.14'
L 8	S 12°47'02"W	16.84'
L 9	S 29°25'43"W	116.21'
L 10	S 30°42'34"W	87.77'
L 11	S 34°04'32"W	89.66'
L 12	S 34°04'52"W	26.13'
L 13	S 44°31'18"W	114.85'
L 14	S 50°43'49"W	103.41'
L 15	S 74°31'37"W	35.46'
L 16	S 64°35'56"E	207.28'
L 17	N 51°56'43"E	227.74'
L 18	N 64°24'39"W	49.79'

N

SCALE 1 INCH = 200 FEET

● = IRON PIN FOUND
○ = IRON PIN SET

20.63 ACRES TO BE CONVEYED TO ASHCRAFT

SURVEY OF FOUR TRACTS
IN SECTION 11 AND
SECTION 17 T.5, R.12
CARTHAGE TOWNSHIP, ATHENS
COUNTY, OHIO
SURVEYED FEB. 1992



John M. Branner
JOHN M. BRANNER P.S. 6805
12500 N. PEACH RIDGE ROAD
ATHENS, OHIO 592-5778