DESCRIPTION OF A 5.00 ACRE TRACT

Situated in Section 24, T.5, R.12, Carthage Township, Athens County, Ohio and being more particularly described as follows:

Beginning at a railroad spike found at the South-west corner of a 5.432 acre tract (330-1280 O.R.), said spike calculated to bear North 84 degrees 00 minutes 48 seconds East, 2186.75 feet from the South-west corner of Section 24;

Thence, along the lines of Doan (267-505 O.R.) and an existing drive

N 8° 29' 34" E, 230.61to an iron pin found;

N 19° 57' 42" W, 205.92 feet to an iron pin set;

Thence, along new lines created by this survey:

S 80° 08' 45" E, 265.37 feet to an iron pin set;

N 60° 07′ 41" E, 252.15 feet to a point in Grantor's East-line, passing an iron pin set at 238.34 feet;

Thence, along the west-line of Bolin (473-136 O.R.)

S 2° 39′ 11″ W, 731.47 feet to a point in Potter Road, passing an iron pin set at 621.61 feet; Thence, along said road:

N 52° 47' 52" W, 140.37 feet;

N 61° 53' 33" W, 174.84 feet:

N 66° 49′ 20″ W, 156.63 feet to the point of beginning and containing 5.00 acres., of which 0.10 acres are out of Parcel # F010010051308 and 4.90 acres are out of Parcel # F010010051307.

Subject to all easements and rights of way of record.

Iron pins set are 5/8 inch by 30 inch long rebar w/ plastic I.D. Cap stamped Branner P.S. 6805 Bearings assumed and are to be used to denote interior angles only

The above description is based on a field survey completed July 2016 by

John M. Branner P.S. 6805

for moson

JOHN M.
BRANNER
S. 6805
ONAL SURVEYOR

