

ROBINSON SURVEYING

MEMBER-PROFESSIONAL LAND SURVEYORS OF OHIO 12355 LIARS CORNER ROAD, MILLFIELD, OHIO 45761

ALAN D. ROBINSON Registered Land Surveyor TELEPHONE (740) 593-8774

DESCRIPTION OF A 6.126 ACRE TRACT

Situated in Section 33, Town 5, Range 12, Carthage Township, Athens County, Ohio, and being a part of a 19.88 acre tract described in Volume 175 Page 705 Official Records of Athens County and being more particularly described as follows:

Commencing at a point at the Southwest corner of Section 33;

thence North 0 degrees 00 minutes 00 seconds East, a distance of 660 feet (Deed) to a point; thence North 90 degrees 00 minutes 00 seconds East, a distance of 544.50 feet (Deed) to a point; thence North 0 degrees 38 minutes 00 seconds East, a distance of 843.49 feet to an iron pin found; thence South 84 degrees 13 minutes 41 seconds East, a distance of 8.89 feet to an iron pin set at a fence corner, said iron pin set being the POINT OF BEGINNING of the following described tract; thence, following an existing fence line, North 4 degrees 25 minutes 11 seconds East, a distance of 325.51 feet to a point in township Road 112, passing an iron pin set and leaving said fence line at 305.22 feet;

thence, following said Road, North 77 degrees 17 minutes 28 seconds East, a distance of 384.79 feet to a point, said point being the point of curvature of a tangent curve, concave to the southwest, having a radius of 220.37 feet, a central angle of 100 degrees 19 minutes 40 seconds, a chord of 338.44 feet and a chord Bearing of South 52 degrees 32 minutes 42 seconds East; thence southeast along said curve, a distance of 385.88 feet (Deed) to an iron pin found, Referenced by an iron pin found Bearing North 2 degrees 22 minutes 48 seconds West, a distance of 29.07 feet (29.04 feet Deed); thence South 2 degrees 22 minutes 52 seconds East, a distance of 272.39 feet (272.59 feet deed) to an iron pin found;

thence, leaving said Road, North 84 degrees 13 minutes 41 seconds West, a distance of 683.89 feet to the POINT OF BEGINNING; said described tract containing 6.126 acres (266,856.0584 square feet).

Bearings are based on previous Surveys and are used to denote angles only.

Subject to all easements and right-of-way of record.

All iron pins set are 5/8 inch by 30-inch long rebar with a yellow cap stamped Alan Robinson RLS 8049.

Alan D. Robinson P.S. 8049 bases the above description on a field Survey completed July 14, 2000,

alan O Holmson

Esscription checked for Mathematical Accuracy ATHENS COUNTY ENGINEER'S OFFICE EY: Requirements of the country o

Alan D.

Robinson

8049

SCISTERS

SCIONAL SUMMER

Instrument 200100001781

