Description Checked for
Mathematical Accuracy
Athens County
ENGINEER'S OFFICE
BY: Reary (Mathematical Accuracy
Athens County
ENGINEER'S OFFICE
DATE: 4/3/11

EXHIBIT A DESCRIPTION FOR A 10.651 ACRE PARCEL

Situated in the State of Ohio, County of Athens, Township of Dover, and being a part of River Lot 334, Section 13, Township 10, Range 14, and being a part of that 87.69 acre tract (Parcel No. G010010040700) as conveyed to Paul E. Brown Trustee (50%) of the Revocable Living Trust of Paul E. Brown dated October 20, 1995 and Donna M. Brown Trustee (50%) of the Revocable Living Trust of Donna M.Brown dated October 20, 1995 by deed of record in Deed Volume 210, Page 71, all reference being to those of record in the Recorder's Office in Athens County, Ohio, said 10.651 acre parcel being more particularly bounded and described as follows:

Commencing at a point at the northwesterly corner of the 100 acre River Lot 335;

Thence along the northerly line of said River Lot 335, **South 85°58'03" East, 2258.98 feet** to a point in the centerline of the Hocking River, said point being a westerly corner of said 87.69 acre Brown tract and being the **Point of Beginning** for the 10.651 acre tract herein described;

Thence along the centerline of said Hocking River and the westerly line of said Brown tract, **North 61°43°21" West, 442.59 feet** to a point at the southerly corner of that 5.3499 acre tract as conveyed to the Athens County Board of Commissioners by deed of record in Deed Volume 372, Page 821;

Thence leaving said centerline and along the southerly line of said Athens County Board of Commissioners tract, North 48°23'01" East, passing 1" iron pipes found at 90.13 feet and 883.80 feet, a total distance of 910.31 feet to a point in the centerline of State Route 13;

Thence along said centerline the following two courses and distances:

South 39°06'03" East, 558.70 feet to a point; and...

South 39°05'58" East, 184.75 feet to a point;

Thence with a new division line across said 87.69 acre tract, South 72°39'11" West, passing iron pins set at 32.30 feet and 645.86 feet, a total distance of 795.86 feet to the Point of Beginning and containing 10.651 Acres, more or less, according to a survey made by Jobes Henderson and Associates, Inc. in February of 2017.

DESCRIPTION FOR A 10.651 ACRE PARCEL

Page 2

The bearings in the above description are based on Ohio State Plane Coordinate System, South Zone, NAD83.

All iron pins set are 5/8" in diameter by 30" in length with red identification caps marked "J&H, PS 8283".

Subject to all valid and existing easements, restrictions and conditions of record.

February 14, 2017 BOK/BOK001/survey/legals/10.651 Acres

Jerenty L. Van Ostran, P.S. Surveyor No. 8283

