Situated in the Northeast quarter of Section 1,
Town 4, Range 13, Lodi Township, Athens County, Ohio,
and being more particularly described as follows:

Commencing at the Northeast corner of Section 1: thence South 1,513.00 feet to a point in the East line of Section 1; thence leaving said line and following County Road 46, S 87 05' W, 1,436.87 feet to a point on the North edge of the road; thence S 63 30' W, 394.40 feet to a point; thence S 35 50' W, 586.05 feet to a point; thence S 57° 23' W, 307.35 feet to a railroad spike in the center of County Road 46, said spike being the real point of beginning for the tract herein described; thence leaving said road S 17° 16' E, 272.00 feet to an iron pin, passing an iron pin at 25.00 feet; thence S 73° 25' W. 183.57 feet to an iron pin; thence N 10°00' W, 272.00 feet to a railroad spike in the center of County Road 46, passing an iron pin at 247.00 feet; thence along the center of said road N 72 44' E. 149.15 feet to the place of beginning and containing 1.035 acres.

Subject to all legal highways and easements on record.

Description prepared by Brian D. McPherson, April, 1979, from a survey by Rex E. Maiden, Reg. Surveyor, # 006296.

Description checked for Mathematical Accuracy ATHENS COUNTY

ENGINEER'S OFFICE

BY: W. M. Walking

DATE: 4/9/79

John S

7. S.

