EXHIBIT A

Description Checked for
Mathematical Accuracy
Athens County
ENGINEER'S OFFICE
BY: Trust Million
DATE: 441/14

LEGAL DESCRIPTION OF AN 8.269 ACRE TRACT

Situated in Section 33, Lodi Township, Town 4, Range 13, Athens County, Ohio and described as follows:

Commencing at a found one and one quarter inch pipe at the estimated and approximate southeast corner of the southwest quarter of Section 34 of Lodi Township; thence along the estimated south line of Section 34 and the north line of Section 33 of Lodi Township

North 86°42'01" West a distance of 1405.76 feet

to a point in Athens County Road 16 at the northwest corner of the Ernest and Shirley Kyle Living Trust (323-1277 O.R.) at the northeast corner of part of lands of Rainbow Lake of Athens County, Inc. (334/375 D.R.) and said point is **THE TRUE POINT OF BEGINNING**; thence leaving said road and along the west line of the Kyle Living Trust (323-1277 O.R.) and the east line of part of said Rainbow Lake of Athens tract (334/375 D.R.)

South 03°36'14" West a distance of 553.42 feet

(passing through a set iron pin at 26.90 feet) to a point at the northeast corner of Christian Broadcasting Ministries (265-1218 O.R.) being witnessed by a found two inch brass cap monument set in concrete which bears South 86°25′20″ East a distance of 0.45 feet; thence along the south line of part of said Rainbow Lake of Athens County tract (334/375 D.R.) and the north line of Christian Broadcasting Ministries (265-1218 O.R.)

North 86°25'20" West a distance of 499.20 feet

to a found two inch brass cap monument set in concrete at the northwest corner of Christian Broadcasting Ministries (265-1218 O.R.); thence along the south line of part of said Rainbow Lake of Athens County tract (334/375 D.R.) and the west line of Christian Broadcasting Ministries (265-1218 O.R.)

South 03°34'51" West a distance of 69.60 feet

to a set iron pin on the easterly right of way of U.S. Route 33 (State of Ohio 332-484 O.R.); thence along said easterly right of way line of U.S. Route 33 (State of Ohio 332-484 O.R.) and the west line of part of the Rainbow Lake of Athens County tract $(334/375 \, \text{D.R.})$ the following four bearings and distances:

North 15°02'22" West a distance of 2.18 feet

to a found two inch aluminum cap monument; thence

North 26°33'23" West a distance of 581.44 feet

to a found three quarter inch rebar, bent at the top but located at the base; thence

North 80°04'37" East a distance of 291.83 feet

to found three quarter inch rebar, bent at the top but located at the base; thence

North 00°44'37" East a distance of 47.56 feet

to a point falling within the right of way of aforesaid Athens County Road 16 on the aforesaid estimated north section line of Lodi Township Section 33,

passing a set iron pin at 17.14 feet; thence along the north line of part of said Rainbow Lake of Athens County tract (334/375 D.R.) and north line of Lodi Township Section 33 and within the right of way of Athens County Road

South 86°42'01" East a distance of 510.64 feet

to the point of beginning and containing 8.269 acres and being part of land described in Volume 334 Page 375 of the Athens County Deed Records.

Note 1) Unless otherwise noted, all set iron pins are 5/8 inch diameter rebar 30 inches in length and capped with a yellow plastic identification marker inscribed: "TOM TRANTINA RLS-8320"

Note 2) All calls for adjoiners cited above and deeds shown in parenthesis are given to fulfill County Auditor and County Engineer's requirements and do not necessarily imply an acceptance of the content of said deeds or the seniority of the same.

The above description was prepared under the supervision of Thomas Trantina, Registered Professional Land Surveyor No. 8320 and based on a survey performed by Southeastern Land Surveys dated March 31, 2014.

Subject to all deeds and right of ways, reservations, restrictive and protective covenants, utility easements and oil, gas and mineral leases of record in the chain of title in Athens County.

The basis of bearing for the above legal description is North 19°18′18″ East between found Ohio Department of Transportation centerline concrete monuments set at stations 37+320.57 and 37+000 (metric) and derived from a GPS survey performed by Robert Canter (a registered surveyor) in 1998 and 1999.

THOMAS C. TRANTINA, P.L.S. #8320 P.O. BOX 121 CHAUNCEY, OHIO 45719

PHONE: 740-797-4499

10m C.
10m C.
3/31/14

