

## SOUTHEASTERN LAND SURVEYS

LEONARD F. SWOYER REGISTERED LAND SURVEYOR

Box 208A Route Five Athens, Ohio 45701 614/593-8701

Situated in Section 34 and Section 28, Fraction 34 of Town 4, Range 13, Lodi Township, Athens County, Ohio and described as follows:

Commencing at a found iron pin, said found iron pin bears Northerly 1438.00 feet from the southwest corner of said Section 28 (by Deed 336 Page 27 of the Athens County Deed Records); thence on an assumed bearing along the east line of said Section 34 and the west line of said Section 28 North 05°56'03" East 938.00 feet to a set iron pin, the northeast corner of a 2.8 acre tract described in Volume 238 Page 540 of the Athens County Deed Records, said iron pin is also THE TRUE POINT OF BEGINNING; thence along the north line of aforesaid 2.8 acre tract North 82°51'11" West 124.00 feet to the northwest corner of said 2.8 acre tract; thence North 82°51'11" West 160.71 feet to a set iron pin; thence North 03°03'17" West 348.36 feet to a set iron pin; thence North 86°36'52" East 343.61 feet to a set iron pin in the east line of said Section 34 and the West line of said Section 28; thence along said section line South 05°56'03" West 298.75 feet to a set iron pin on the north side of Lodi Township Road 529 said set iron piris also on the northerly property line of a 25.20 acre tract described as Tract 2 in Volume 292 Page 225 of the Athens County Deed Records; thence along said northerly property thence South 65°03'57" Fast 432.00 feet to a point; thence South 81°03'57" East 675.00 feet to a point; thence South 83°33'37" East 166.81 feet to a point on the west right of way of State Route 33; thence along said west right of way South 04°38'22" East 15.31 feet to a point 210 feet right of Station 1302+00 of the center line of a survey made by the Ohio Department of Transportation in 1979 of State Route 33 in said Lodi Township; thence continuing along said west right of way South 84°08'52" East 134.63 feet to a point 85 feet right of Station 1302+50 of aforesaid line survey; thence continuing along said west right of way South 20°53'30" East 15.78 feet to a point on the southerly line of a 25 foot right of way mentioned in the second tract of Volume 292 Page 225 of the Athens County Deed Records; thence along said southerly rihgt of way North 84°33'37" West 309.19 feet to a point, the northeast corner of a 22.70 acre tract described in the second tract of Volume 238 Page 540 of the Athens County Deed Records; thence along the north property line of said 22.70 acre tract North 78°41'29" West 1,089.50 feet to a set iron pin on the west line of Section

7

28, the point of beginning, containing 5.5292 acres there being 2.6996 acres in Section 34 and 2.8296 acres in Fraction 34 of Section 28.

Note: All set iron pins are 5/8 inch diameter rebar 30 inches in length.

The above description was written by Leonard F. Swoyer Registered Professional Land Surveyor Number 6765 and based on a survey prepared by Southeastern Land Surveys dated April 14, 1986.

Subject to all easements and right of ways of record.

Description checked for Mathematical Accuracy ATHENS COUNTY

ENGINEER'S OFFICE

DATE: 4/15/86

