



| Line | Bearing | Distance |
|------|--------------|----------|
| 1 | S 58°00'03"E | 126.22' |
| 2 | S 56°32'04"E | 93.12' |
| 3 | S 52°54'46"E | 76.35' |
| 4 | S 39°00'20"E | 69.45' |
| 5 | S 24°57'41"E | 101.30' |
| 6 | S 32°33'34"E | 23.80' |
| 7 | S 32°33'34"E | 58.96' |
| 9 | S 48°05'37"E | 70.36' |
| 10 | S 48°05'37"E | 89.09' |
| 11 | S 48°05'37"E | 145.64' |
| 12 | S 49°44'07"E | 95.33' |
| 13 | S 0°13'08"W | 25.79' |

PARCELS GREATER THAN 5 AC
W/ EXISTING ROAD FRONTAGE -
NO APPROVAL REQUIRED.
Bob Eichenberg
1-5-04

Description Checked for
Mathematical Accuracy
Athens County
ENGINEER'S OFFICE
BY: S. Blause
DATE: 11-24-03

OK TO TRANSFER
ATHENS CITY-COUNTY HEALTH DEPT.
Michael Cooper R.S.
12/4/03

SURVEY OF 4 TRACTS
IN SECTION 23, T.4, R.13,
LODI TOWNSHIP
ATHENS COUNTY, OHIO
SURVEYED NOV., 2003

BY: John M. Branner
JOHN M. BRANNER P.S. 6805
12500 N. PEACH RIDGE ROAD
ATHENS, OHIO 45701
(740) 592-5778



SCALE 1 INCH = 200 FEET
● = IRON PIN SET
○ = IRON PIN FD.
ASSUMED BEARINGS
TO BE USED TO DENOTE
INTERIOR ANGLE ONLY