

SOUTHEASTERN LAND SURVEYS

LEONARD F. SWOYER REGISTERED LAND SURVEYOR

Box 208A Route Five Athens, Ohio 45701 614/593-8701

Situated in Fraction Lot 34, Section 28, Town 6, Range 12, Rome Township, Athens County, Ohio and being more particularly described as follows:

Commencing at a found stone at the intersection of the center line and north line of Fraction Lot 34; thence along the center of said Fraction an assumed bearing South 807.92 feet to a set railroad spike in the center of Rome Township Road 231 and the point of beginning: thence along said road northeasterly a distance of 276.23 feet following a curve concave to the south and not tangent with the last described line, said curve has a radius of 486.167 feet, a central angle of 32 degrees 33 minutes 17 seconds, and the chord of said curve bears North 81 degrees 19 minutes 38 seconds East 272.55 feet; thence continuing along said road North 65 degrees 03 minutes 01 seconds East on a line tangent to said curve 232.66 feet to a set railroad spike: thence North 65 degrees 19 minutes 47 seconds East 342.93 feet to a set railroad spike; thence leaving said road South along the west property line of a tract described in Volume 336 Page 129 of the Athens County Deed Records (passing set iron pins at 13.05 feet. 205.90 feet and 871.12 feet) for a total distance of 1678.83 feet to a set iron pin on the south line of rraction Lot 34; thence South 89 degrees 45 minutes 34 seconds west along the south line of said Fraction and the north property line of a tract described in Volume 310 Page 353 of the Athens county Deed Records (passing a set iron pin at 600.22 feet) for a total distance of 792.00 feet to a set iron pin; thence North along the east line of a tract described in Volume 232 Page 124 of the Athens County Deed Records (passing set iron pins at 305.15 feet, 553.01 feet and 1380.78 feet) for a total distace of 1399.78 feet to the point of beginning containing 27.4103 acres and being a more accurate description of a tract described in Volume 348 Page 113 of the Athens County Deed Records. Note: All set iron pins are & inch in diameter and 31 inches in length.

SUBDIVISIONS

The above description was based on a survey done by Southeastern Land Surveys, Leonard F. Swoyer Registered Surveyor Number 6765, dated May 21, 1982.

> ascription checked for Butchematical Accuracy THENS COUNTY

ENGINEER'S OFFICE

