REVISED DESCRIPTION LOT 4 -- JAMES R. MORRIS

Point of beginning being a nail in the center of Troy Township Road 161-A and in the line of James R. & Gloria A. Morris and George E. Heiney, where a stone marking the center of Section 19 bears N 27^o 52' W 865.00 feet; thence leaving the line of said Heiney,

N 0° 46 30 W 700.00 feet to a 5/8 inch iron pin set, passing a 5/8 inch iron pin set at 19.20 feet; thence,

 $S 89^{\circ} 13^{\circ} 30^{\circ} W 83.85$ feet to a 5/8 inch iron pin set: thence,

N 0° 46 30 W 480.00 feet to a 5/8 inch iron pin set; thence,

N 89° 13′ 30″ E 463.09 feet to a 5/8 inch iron pin set in the line of Arnold N. Spencer; thence with the line of said Spencer,

S 0° 46 30" E 1020.60 feet to a nail in the center of Township Road 161-A, a corner to said Morris, Heiney and Spencer, passing an iron pipe found at 997.55 feet; thence with the center of Township Road 161-A and in the line of said Heiney,

S 61° 09' 07" W 220.16 feet to a nail; thence,

S 68° 16' 06" W 94.95 feet to a nail; thence,

S 76° 27' 07" W 98.76 feet to the place of beginning.

Containing 10.615 acres more or less as shown as Lot No.4 on the Plat of Survey attached hereto and made a part hereof by reference.

As surveyed April 1983 by Curtis A. Lucas, Registered Land Surveyor No.5930, State of Ohio.

P.R.- 372-907

pescription checked to

Mathematical Accuracy,


ATHEMS COUNTY

ENGINEER'S OFFICE

(O · C+

6-14-88

22



SURVEYED APRIL 1983 BY TIMOTHY P. ROUSH UNDER THE SUPERVISION OF: ___

OHIO REGISTRATION NO. 5930

23