

SOUTHEASTERN LAND SURVEYS

LEONARD F. SWOYER REGISTERED LAND SURVEYOR

Box 208A Route Five Athens, Ohio 45701 614/593-8701

Situated in Section 31 and Section 25, Town 5 North, Range 11 West, Troy Township, Athens County, Ohio and described as follows:

Commencing at a found stone at the southeast corner of said Section 31, said found stone being THE TRUE POINT OF BEGINNING; thence along the south line of said Section 31 and the south property line of a 53.41 acre tract described in Volume 354 Page 623 of the Athens County Deed records and the north property line of a 133 acre tract described in Volume 227 Page 001 of the Meigs County Deed Records North 90°00'00" West (passing a set iron pin at 105.30 feet) for a total distance of 314.01 feet to a found iron pin the southeast corner of a 1.00 acre tract described in Volume 372 Page 919 of the Athens County Deed Records; thence along the east property line of said 1.00 acre tract North 00°00'00' East 208.71 feet to a found iron pin the northeast corner of said 1.00 acre tract; thence along the north property line of said 1.00 acre tract North 90°00'00'' West 158.71 feet to a point on the east line of a 50 foot easement described in Volume 372 Page 919 of the Athens County Deed Records; thence leaving the north property line of said 1.00 acre tract and along the east side of said 50 foot easement North 00°00'00'' East 90.00 feet to a set iron pin; thence North 90°00'00'' East 435.60 feet to a set iron pin; thence South 00°00'00'' East 90.00 feet to a set iron pin; thence North 90°00'00'' East 140.53 feet to a set iron pin; thence South 00°00'00'! East 208.71 feet to a set iron pin on the south line of aforementioned Section 25; thence along the south line of said Section 25 and the north line of Section 30 of Meigs County North 90°00'00''West 103.41 feet to the point of beginning containing 2.9000 acres there being 2.4045 acres in Section 31 and 0.4955 acres in The above 2.9000 acres is part of a 53.41 acre tract described in Volume 354 Page 623 of the Athens County Deed Records.

Note: All set iron pins are capped, 5/8 inch diameter rebar 30 inches in length.

The above description was written by Leonard F. Swoyer Registered Professional Land Surveyor Number 6765 and based on a survey prepared by Southeast-

| ray #31



SOUTHEASTERN LAND SURVEYS

LEONARD F. SWOYER REGISTERED LAND SURVEYOR

Box 208A Route Five Athens, Ohio 45701 614/593-8701

ern Land Surveys dated April 11, 1985.

Subject to all easements and right of ways of record.

Description checked for Mathematical Accuracy ATMENIS COUNTY

15. 5-28-85

