Description Checked for
Mathematical Accuracy
Athens County
ENGINEER'S OFFICE
BY:
DATE: 417/15

DESCRIPTION OF A 15.45 ACRE TRACT

Situated in Section 19, T.11, R.15, Waterloo Township, Athens County, Ohio and being a part of a tract of land as described in Vol.175, Page 787 Official Records and being more particularly described as follows:

Commencing at a stone found, said stone bears South 89 degrees 35 minutes 32 seconds East, 125 feet from a stone found at the North-west corner of Section 19:

Thence, along the North-line of Section 19,

S 85° 54' 25" E, 1297.41 feet to a stone found;

Thence, along the west-line of Preston (353-979 O.R)

S 4° 07' 03" W, 500.00 feet to an iron pin previously set and being the point of beginning for the tract of land herein described:

Thence, along the South-line of Loftis (501-967 O.R.)

N 85° 54' 25" W, 1146.98 feet to an iron pin previously set;

S 4° 07' 03" W, 631.58 feet to a point in State Route 681, passing an iron pin previously set at 590.00 feet;

Thence, along State Route 681 and new lines created by this survey;

S 41° 30' 44" E, 28.36 feet;

S 38° 02' 52" E, 99.28 feet;

S 29° 19' 35" E, 137.05 feet;

Thence, leaving State Route 681

S 74° 12' 41" E, 34.28 feet to an iron pin set south of existing culvert;

N 62° 29' 7" E, 1116.88 feet to a point in Grantor's East-line, passing an iron pin set at 1108.91 feet; Thence, along the west-line of Preston (353-979 O.R.)

N 4° 07' 3" E, 261.01 feet to the point of beginning and containing 15.45 acres.

Subject to all easements and rights of way of record

Iron pins set are 5/8" by 30" long rebar with plastic I.D. cap Stamped "Branner P.S. 6805"

Bearings based on Grid North N.A.D. 83

The above description is based on a field survey completed April 2015 by

John M. Branner P.S. 6805

Ma /h

