

Situate in Section 8, T-11, R-15, Waterloo Twp., Athens County, Ohio, and being more particularly described as follows, to wit:

Commencing at a stone at the Northwest corner of Section 8, thence with the west line of Section 8, S 0° 42' 56" W, 1666.38 feet to the point of beginning; thence S 89° 17' 04" E, 727.26 feet to an iron pin in the center of Township Road T-25; thence with Township Road T-25, S 3° 34' 10" W, 266.23 feet to an iron pin in the east edge of T-25; thence with T-25, S 24° 20' 40" W, 329.18 feet to an iron pin in the west edge of T-25; thence continuing with T-25, S 3° 34' 25" W, 488.30 feet to an iron pin in the center of T-25; thence N 89° 25' 00" W, 557.72 feet to a R.R. tie corner post, ^{in the West line of Section 8} passing an iron pin at 16.42 feet; thence with the west line of Section 8, N 0° 42' 56" E, 1056.44 feet to the point of beginning and containing 15.2742 Ac.

Subject to highways and easements of record.

Description prepared from a survey by Gerald E. Hann 5-5062.

Sec #8 Waterloo

BY: *Garb Shields*
DATE: *June 27-73*

14

Situate in Sec 8, T-11, R-15, Waterloo Twp,
Athens County, Ohio, and being more particularly
described as follows, to wit:

Beginning at a stone at the Northwest Corner
of Sec. 8, ^{along the North line of Section 8} thence $S 89^{\circ} 06' 52'' E$, 783.80 feet to an
iron pin in the center of Township Road T-25;
thence with said Township Road T-25 and
Jack B. Sickles West line (D.B. 345, P 121), $S 2^{\circ} 34' 00'' W$,
674.03 feet to an iron pin; thence continuing
with said T-25 and said Sickles West line,
 $S 2^{\circ} 09' 00'' W$, 70.04' to an iron pin; thence
continuing along said T-25, $S 0^{\circ} 31' 10'' W$, 70.46'
to an iron pin; thence leaving said T-25
 $N 89^{\circ} 17' 04'' W$, 760.29 feet to a point in the
west line of Section 8; thence along the west
line of Section 8, $N 0^{\circ} 42' 56'' E$, 816.47 feet
to the point of beginning and containing
14.4236 Ac.

Subject to High ways and easements of
record.

Description prepared from a survey by
Gerald E. Hann S-5062.

793.22
23.25
816.47

Description checked for
Mathematical Accuracy
ATHENS COUNTY
ENGINEER'S OFFICE

BY: Robert Shultz
DATE: June 22-78

15

"B"

Situate in Sec 8, T-11, R-15, Waterloo Twp., Athens County, Ohio, and being more particularly described as follows, to wit: Commencing at a stone at the Northwest corner of Section 8, thence with the West line of Section 8, S 0° 42' 56" W, 816.47 feet to the point of beginning; thence S 89° 17' 04" E, 760.29 feet to an iron pin in the center of Township Road T-25; thence with Township Road T-25, S 0° 31' 10" W, 175.15 feet to an iron pin, passing an iron pin at 69.75'; (I.P. is 22'-9" from the center of a 24" Maple tree); thence continuing along T-25, S 3° 34' 10" W, 675.58 feet to an iron pin; thence N 89° 17' 04" W, 727.26 feet to a point in the west line of Section 8; thence N 0° 42' 56" E, 849.91 feet to the point of beginning and containing 14.5840 Ac.

Subject to Highways and easements of record.

Description prepared from a survey by Gerald E. Hann, S-5062.

Sec 8

762.16
19.00

Reviewed and checked for
 Mathematical Accuracy
 Date June 22-78
 [Signature]

WAT#8

16

STONE 7
N.W. COR.
SEC. 8
N. 4774.00

N. LINE SEC. 8
S 89° 06' 52" E, 783.80'

15.11
I.P.(F)

JACK B. & SHARON R.
SICKLES
345-121

(14.4236 AC.)

N 0° 42' 56" E, 816.47'

S 2° 34' 00" W, 674.03'

S 2° 09' 00" W, 70.04'
I.P.(F)
20.00'

S 0° 31' 10" W, 70.46'
I.P.(S)

N 89° 17' 04" W, 760.29'

S 0° 31' 10" W, 175.15'
I.P.(S)

FRANK H. BROWN et al
340-685

(14.5840 AC.)
(E)

N 0° 42' 56" E, 849.91'

S 3° 34' 10" W, 675.58'



17

N 89° 17' 04" W, 727.26'

I.P.(S)
I.P. & witness (Move 18' 50")

W LINE SEC. 8

S 3° 34' 10" W, 266.23'

(A)

(15.2742 AC.)

N 0° 42' 56" E, 1056.44'

S 24° 20' 40" W, 322.18'
I.P.(S)

EDNA H. SMITH
215-536
274-123 & 125

R.R. TIE
CORNER POST

N 89° 25' 00" W, 557.72'

S 3° 34' 25" W, 488.30'

I.P.(F)
I.P.(S)
85° 35'
16.42'
46.41'
20.15'

THOMAS A. & WANDA B.
ROBERTSON
335-819

JAMES &
HELEN M.
SECOY
292-123

18

DATE 6-78 SCALE 1"=100'	SURVEY FOR FRANK BROWN et al NEW MARSHFIELD, OHIO	BY GERALD E. HANN 21 ELMWOOD PL. ATHENS, OHIO	SECTION 8, T-11, R-15 WATERLOO TOWNSHIP ATHENS COUNTY OHIO	
----------------------------------	---	--	---	--

STONE 7
N.W. COR.
SEC. 8

N. LINE SEC. 8
S 89° 06' 52" E, 783.80'

15.11'
R
I.P.(F)

JACK B. & SHARON R
SICKLES
345-121

(14.4236 AC.)

N 0° 42' 56" E, 816.47'

S 2° 34' 00" W, 674.03'

S 2° 09' 00" W
70.04'

S 0° 31' 10" W
70.46'

20.00'
I.P.(F)
18.00'
I.P.(S)

113.92' 183.90' 444.47'
N 89° 17' 04" W, 760.29'

S 0° 31' 10" W
175.15'

I.P.(S)

FRANK H. BROWN et al
340-685

(12.5840 AC.)

N 0° 42' 56" E, 694.28'

S 3° 34' 10" W, 591.58'



1" = 100'

25

83° 41' 00" W 734.95'
N 89° 17' 04" W 781.46'

(2.000 AC.)

155.63'

84.00'
I.P.(S)

165.69' 136.21' 112.97' 312.39'
N 89° 17' 04" W, 727.26'

S 3° 34' 10" W
266.23'

I.P.(S)

1212.07'

(15.2742 AC.)

17.2742 AC.

N 0° 42' 56" E, 1036.44'

I.P.(S)

EDNA H. SMITH
274-123 & 125

RR TIE
CORNER POST

N 89° 25' 00" W, 557.72'

JAMES & HELEN M
SECOY
292-123

85° 35'
16.42' 46.41'
I.P.(F)
I.P.(S)

THOMAS A. & WANDA B.
ROBERTSON
335-819

S 3° 34' 25" W, 488.3'

26

DATE 6-78 SCALE 1"=100'	SURVEY FOR FRANK BROWN et al NEW MARSHFIELD, OHIO	BY GERALD E. HANN 21 ELMWOOD PL. ATHENS, OHIO	SECTION 8, T-11, R-15 WATERLOO TOWNSHIP ATHENS COUNTY OHIO	Gerald E. Hann S 5062
----------------------------------	---	--	---	--------------------------