## Legal Description Pre-Approval APPROVED

All transfers are subject to Athens County Conveyance Standards

DEC 2 2 2015

Description Checked for Mathematical Accuracy Athens County ENGINEER'S OFFICE 12/21/15 DATE:

## Jill Thompson Athens County Auditor

## **DESCRIPTION OF A 47.954 ACRE TRACT**

Section 23, T.6, R.13, Ames Township, Athens County, Ohio and being parts of Tract 1 (C010010027400) and Tract 2

(C010010027700) as described Volume 303, Page 2522 of the Official Records of Athens County and being more particularly described as follows:

Beginning at an iron pin found at the South-west corner of Section 23

Thence, along the west-line of said Section 23:

N 4° 19' 58" E, 1997.51 feet to a stone;

N 3° 44' 19" E, 1255.56 feet to an iron pin found;

Thence, along the lines of Greenfield (226-746 O.R.)

N 40° 08' 30" E, 766.91 feet to a point in Hooper Ridge Road, passing an iron pin found at 730.28 feet;

Thence, along said road:

S 37° 46' 37" E, 44.86 feet;

S 34° 06' 37" E, 14.98 feet;

Thence, leaving said road and along new lines created by this survey:

S 52° 05' 13" W, 39.07 feet to an iron pin set;

S 11° 35' 38" E, 1166.79 feet to an iron pin set;

S 67° 46' 58" E, 41.70 feet to a point in Bryson Road;

Thence, along said road:

S 22° 13' 02" W, 44.17 feet;

S 15° 45' 25" W, 39.75 feet;

S 10° 33' 35" W, 192.63 feet;

S 12° 39' 43" W, 137.64 feet;

S 11° 43' 11" W, 256.72 feet;

S 1° 43' 19" W, 399.29 feet;

S 20° 57' 59" W, 108.50 feet;

S 29° 13' 44" W, 128.80 feet;

S 42° 26' 58" W, 123.03 feet;

S 47° 50' 35" W, 134.23 feet;

S 42° 36' 30" W, 153.43 feet;

S 22° 25' 20" W, 212.89 feet; S 2° 21' 1" W, 137.57 feet;

S 4° 45' 42" E, 77.07 feet;

S 10° 03' 20" E, 274.17 feet;

S 0° 22' 55" W, 197.50 feet;

S 13° 11' 16" W,48.89 feet;

S 23° 59' 15" W,125.22 feet;

S 34° 02' 21" W,19.37 feet;

Thence, leaving said road and along the South line of Section 23

N 87° 14' 23" W, 353.72 feet, passing an iron pin found at 15.00 feet, to the point of beginning and containing

Subject to all easements and rights of way of record.

Iron pins set are 5/8'x 30" rebar w/ plastic I.D. cap stamped Branner P.S. 6805

Bearings: Grid North, N.A.D. 83

The above description is based on a field survey completed December 2015 by

John M. Branner P.S. 6805

An m



