EXHIBIT "A"

Being a part of tract of land that is now or formerly in the name of Mary J. Harris, as recorded in Official Record 174 at page 252, Athens County Recorder's Office, said tract being situated in Section 3, T6N, R13W, Ames Township, Athens County, State of Ohio, and being more particularly described as follows:

Beginning at an iron pin found on the grantor's north line, from which the northwest corner of Lot 93 of "Patterson's Addition", as recorded in Volume 3 at page 14, bears South 23 degrees 48 minutes 16 seconds East a distance of 498.83 feet;

Thence with a new line through the grantor's land, South 32 degrees 21 minutes 31 seconds West a distance of 238.12 feet to a 5/8" X 30" iron pin with a plastic identification cap set;

Thence continuing with a new line through the grantor's land, North 82 degrees 36 minutes 27 seconds West passing through a 5/8" X 30" iron pin with a plastic identification cap set at 288.26 feet, going a total distance of 318.26 feet to a point on the east bank of Federal Creek and the grantor's west line;

Thence along the east bank of Federal Creek, and the grantor's west line, the following two courses:

- 1. North 19 degrees 22 minutes 58 seconds East a distance of 155.25 feet to a point, and;
- 2. North 38 degrees 18 minutes 05 seconds East a distance of 165.25 feet to a point being the grantor's northwest corner from which an iron pipe found bears, North 68 degrees 09 minutes 01 seconds West a distance of 80.74 feet;

Thence leaving the east bank of Federal Creek, and along the grantor's north line, South 68 degrees 09 minutes 01 seconds East passing through a 5/8" X 30" iron pin with a plastic identification cap set at 5.00 feet, going a total distance of 311.50 feet to the point of beginning containing 2.005 acres, more or less, and subject to the right-of-way of State Route 329 and all easements of record.

The bearings used in the above described tract are assumed and are for the determination of angles only.

The above described tract was surveyed by George F. Seymour, Ohio Professional Surveyor No. 6044, in August of 1999.

George F. Seymour, P.S. #6044

Description checked for Mathematical Accuracy ATHENS COUNTY ATHENS OFFICE

GEORGE F. O. SEYMOUR S.6044 X. GISTERU RVEYOUNING



A MS #3

Tuesday, October 05, 1999 9:04 am. Pg: 1

"Sight" Survey 980312-Z-0312 Registered to: athens county engineers dept File Name: Untitled

Precision Ratio Length Traversed Length To Close

	Point	Direction	Distance	Northing	Easting	Elevation
Database	opened	i: Tuesday, October 0	5, 1999 8:58 am.			
Assigned	point					
G4 - 4	1			5000.00000	5000.00000	0.000
Start	1			5000 00000	5000 00000	. 0 000
Raw:	_	2.2131w	238.12	5000.00000	5000.00000	0.000
TR		S 32°21'31.0" W	238.120			
	2			4798.85652	4872.55419	0.000
Raw:		2.4627w	318.26			
TR		N 82°46'27.0" W	318.260			
	3	2220	455.05	4838.88743	4556.82178	0.000
Raw:		9.2258e N 19°22'58.0" E	155.25			
ΓR	4	N 19 22 38.0 E	155.250	4985.33825	4608.34578	0.000
Raw:	•	8.1805e	165.25	4903,33023	4006.343/8	0.000
TR		N 38°18'05.0" E	165.250			
	5			5115.02006	4710.76741	0.000
Raw:	s68	3.0901e	311.50			
ΓR		S 68°09'01.0" E	311.500			
	6			4999.08803	4999.89024	0.000
N		N 6°51'45.0" E	0.919	5000 00000	F500 00000	
	1			5000.00000	5000.00000	0.000
	Adjuste	ed Points				
Go to	1			5000.00000	5000.00000	0.000
EP	-	S 38°18'05.0" W	10.000		Bng. (B.S. is "BS	
Start					8	,
	1			5000.00000	5000.00000	0.000
law:		2.2131W	238.12			
R	2	S 32*21'31.0" W	238.120	4798.85652	4973 55410	0.000
law:		2.3627W	318.26	4/ 90:03032	4872.55419	0.000
R		N 82*36'27.0" W	318.260			
	3			4839.80569	4556.93956	0.000
law:		9.2258E	155.25			
TR.		N 19°22'58.0" E	155.250	****		
law:	4	8.1805E	165.25	4986.25650	4608.46356	0.000
R		1 38°18'05.0" E	165.250			
	5	1 30 10 03.0 L	103.230	5115.93832	4710.88519	0.000
law:	_	3.0901E	311.5	0110170002	4710.00317	0.000
R		S 68°09'01.0" E	311.500			
_	6			5000.00629	5000.00803	0.000
N		S 51°55'55.8" W	0.010			
	1			5000.00000	5000.00000	0.000
eee - 07	252 002	C. Foot - 2.007 4				
1ca = 87	352.803	Sq. Feet or 2.005 Ac	res			

1:1.19E+23 1188.390 0.000

