## DESCRIPTION OF A 0.311 ACRE TRACT

Situated in L.L. 122, Section 26, T. 9, R. 14, Athens Township, Athens County, Ohio and being a portion of platted lot #3 of Heatherstone Subdivision East of the existing fence line and being more particularly described as follows;

Commencing at the North-east corner of lot #3 of Heatherstone Subdivision, said point being the POINT OF BEGINNING; thence, South 4 degrees 25 minutes 19 seconds West, a distance of 513.34 feet to a point; thence, North 38 degrees 02 minutes 18 seconds West, a distance of 37.34 feet to an iron pin set in the East fence line; thence, following said fence line, North 1 degree 27 minutes 05 seconds East, a distance of 109.61 feet to a point; thence, North 5 degrees 11 minutes 33 seconds East, a distance of 254.62 feet to a point; thence, North 9 degrees 24 minutes 51 seconds East, a distance of 121.82 feet to an iron pin set; thence, leaving said fence line, South 86 degrees 51 minutes 05 seconds East, a distance of 16.86 feet to the POINT OF BEGINNING; said described tract containing 0.311 acre (13586.40 SF.).

Subject to all easements and right of way of record. All iron pins set are 5/8 inch by 30 inch long rebar.

The above description is based on a field survey completed June 1997 by John M. Branner P.S. 6805

Description checked for Mathematical Accuracy ATHEN'S COUNTY ENGINEER'S OFFICE BY:

