



LINE	BEARING	DISTANCE
L 1	S 84° 22' 06" E	74.21'
L 2	S 76° 13' 24" W	87.32'
L 3	N 83° 44' 01" W	64.01'
L 4	N 53° 24' 43" W	40.55'

CURVE	DELTA ANGLE	RADIUS	ARC	TANGENT	CHORD	CHORD BEARING
1	09° 59' 39"	1527.89'	266.51'	133.60'	266.18'	N 84° 18' 43" E
2	36° 23' 47"	1527.89'	970.57'	502.29'	954.34'	S 72° 26' 34" E
11	46° 23' 26"	1527.89'	1237.09'	654.71'	1203.57'	S 77° 28' 24" E
12	09° 02' 29"	1565.89'	247.10'	123.81'	246.84'	N 57° 55' 58" W

PLAT SHOWING THREE PARCEL
IN L.L. 30 AND 47 SECTION 11
T. 9. R. 14. ATHENS TOWNSHIP
ATHENS COUNTY, OHIO
SURVEYED NOV. 1995
JOHN M. BRANNER P.S. 6805
12500 N. PEACH RIDGE ROAD
ATHENS, OHIO 614-592-5778

SCALE 1 INCH = 100 FEET
O • IRON PIN SET

