ROBINSON SURVEYING

MEMBER-PROFESSIONAL LAND SURVEYORS OF OHIO 12355 LIARS CORNER ROAD, MILLFIELD, OHIO 45761

ALAN D. ROBINSON Registered Land Surveyor

TELEPHONE (740) 593-8774

DESCRIPTION OF A 39.231 ACRE TRACT

Situated in Section 17, Town 7, Range 12, Bern Township, Athens County, Ohio, and being a 37.90 acre tract Described in Volume 313 Page 25 Athens County Deed Records and being more particularly described as follows:

Commencing at the Southwest corner of Section 17;

thence, South 84 degrees 20 minutes 49 seconds East, a distance of 2054.09 feet (Deed) to an iron pin found:

thence, North 5 degrees 39 minutes 11 seconds East, a distance of 690.36 feet to a to an iron pin set said iron pin set being the POINT OF BEGINNING of the following described tract;

thence, North 5 degrees 39 minutes 11 seconds East along said line, a distance of 2588.53 feet to the point in State route 50-A, passing an iron pin found at 798.68 feet, an iron pin set at 1578.66 feet and an iron pin set on State rout 50-A Southern right-of-way at 2558.13 feet, said point being the point of curvature of a non-tangent curve, concave to the southwest, having a radius of 819.02 feet, a central angle of 41 degrees 41 minutes 38 seconds, and a chord of 582.93 feet bearing South 54 degrees 22 minutes 52 seconds East:

thence, following said State route, southeast along said curve, a distance of 596.00 feet to a point; thence, leaving said State route, South 55 degrees 28 minutes 26 seconds West, a distance of 239.14 feet (236.79 feet Deed) to an iron pin found, passing iron pins found at 39.77 feet and at 162.78 feet;

thence, South 46 degrees 56 minutes 27 seconds East, a distance of 331.53 feet (331.62 feet Deed) to an iron pin found;

thence, North 5 degrees 08 minutes 13 seconds East, a distance of 254.55 feet (252.94 feet Deed) to a point in the aforementioned State route, passing an iron pin set on the Southern right-of-way at 204.83 feet;

thence, following said State route, South 31 degrees 58 minutes 26 seconds East, a distance of 76.62 feet to a point;

thence, leaving said State route, South 60 degrees 33 minutes 14 seconds West, a distance of 34.10 feet to an iron pin found, passing an iron pin found at 30.15 feet;

thence, South 5 degrees 12 minutes 57 seconds West, a distance of 387.76 feet (388.24 feet Deed) to an iron pin found, passing an iron pin found at 210.01 feet;

thence, South 84 degrees 48 minutes 55 seconds East, a distance of 249.00 feet (250.00 feet Deed) to an iron pin found; thence, South 5 degrees 18 minutes 42 seconds West, a distance of 1404.19 feet to an iron pin set, passing an iron pin set at 545.82 feet;

thence, South 80 degrees 25 minutes 05 seconds West, a distance of 443.50 feet to an iron pin set; thence, South 69 degrees 55 minutes 05 seconds West, a distance of 482.50 feet to the POINT OF BEGINNING; said described tract containing 39.231 acres (1,708,884.1930 square feet).

Bearings are based on a survey of a 1.79-acre tract.

Subject to all easements and right-of-way of record.

All iron pins set are 5/8 inch by 30-inch long rebar with a yellow cap stamped Alan Robinson RLS 8049.

The above description is based on a field Survey completed January 2000, By Alan D. Robinson P.S. 8049, 12355 Liars Corner Road, Millfield, Ohio 45761 (740) 593-8774

alan D Robinson

Description checked for Mathematical Accuracy ATHENS COUNTY ENGINEER'S OFFICE
BY: S. Blause
DATE: 2-23-



