

C. THOMAS SMITH

and Associates Surveying

P. O. BOX 393 Racine, Ohio 45771

DESCRIPTION OF SURVEY FOR HARRY MINTHORNE

Being a part of a 94+ acre tract of land transferred to Charles D. Guthrie and John S. Guthrie as recorded in Deed Book 362, at Page 865, Athens County Recorder's Office, Athens County, Ohio, said tract being a part of the South half of Section 24, Township-5-North, Range-13-West, Gannan Township, Athens County, State of Ohio and more particularly described as follows:

Beginning at an existing 5/8" iron pin found, being a corner on the North line of said $94\pm$ tract which bears North $82^\circ36'20"$ West a distance of 2845.97 feet and South $07^\circ14'34"$ West a distance of 288.79 feet from a stone found at the Northeast corner of said $94\pm$ acre tract:

Thence leaving said North line South $07^{\circ}23'52"$ West passing thru a 5/8" iron pin set at a distance of 732.99 feet and going a total distance of 752.74 feet to a point in the centerline of County Road #20;

Thence along said centerline the following six courses:

- 1. North 75°11'29" West passing thru an existing 5/8" iron pin found at a distance of 42.85 feet and going a total of 145.38 feet to a P.K. nail found;
- 2. North 84°58'28" West a distance of 143.75 feet to a P.K. nail found;
- South 81°53'23" West a distance of 170.63 feet to a P.K. nail found;
- 4. North 87°34'11" West a distance of 89.53 feet to a P.K. nail found;
- 5. North 71°29'57" West a distance of 101.47 feet to a P.K. nail found;
- 6. North $54^{\circ}01'20"$ West a distance of 146.89 feet to a 5/8" iron pin found;

Thence leaving said centerline North 10°38'46" East a distance of 667.71 feet to a 5/8" iron pin set;

Thence South 85°29'06" East a distance of 733.05 feet to the principal point of beginning containing 12.7325 acres to all legal easements and rights-of-way.

Bearings used in the above description were derived from magnetic taken October 20, 1986.

The above description was prepared from an actual survey made on the 27th day of October, 1989, by C. Thomas Smith, Ohio Professional Surveyor #6844.

Description cnecked for Mathematical Accuracy ATHENS COUNTY

DATE:

ENGINEER'S OFFICE

11-13-59

C. Thomas Smith, P.S. #6844

CAN#24



C. THOMAS SMITH

and Associates Surveying

P. O. BOX 393

Racine, Ohio 45771

BEING A PAINT OF THE SOUTHEAST QUADTER OF SECTION 24, TOWNSHIP - 3 - MORTH, RANGE -13 - WEST CANAAN TOWNSHIP, ATHENS COUNTY, STATE OF BAND

NOTE: BEARINGS DERESED FROM MAGNETIC

TAILEN 10-20-56.

T.A. & S. C. PRICE

3.5-508

SCALC /"=100"

20.55

S 85° 29' 36" E

12.7325 ACRUET

96.60, COUNTY ROAD #20 TO 632"W)
N71029'57"W N87084'11"W

LEGEND OFEXISTING SIE LRONPINS DEKISTING P.K. NAILS

€-5/8" IRON PIN SET

D. EXISTING STONE

· - POINT

CANMAN TWIP. TAX PCAT I U.S.G.S. TO PO MAPS PLAT BOOK 3 PAGE 138 PLAT BOOK 6 PAGE 392 DOEDS! AS MOTED ON PLAT 143.74' 102.53' 42.85 V N84°58' 28"VI NISOII: 29"W 145.38

> V. GOEDICKE 270-297 / 245-608

PLAT PREPARED FROM AN ACTUAL SUMMEY MADE OFFICE 27th DAY OF OCTOBER, 1989 BY

OHIO PROFESSIONAL SURVEYOR

No 6844

18