



LINE	BEARING	DISTANCE
L 1	S 39°50'56"E	56.53'
L 2	S 34°59'15"E	100.84'
L 3	S 27°32'57"E	97.96'
L 4	S 23°35'12"E	102.46'
L 5	S 23°35'12"E	63.92'
L 6	N 15°52'23"W	104.39'
L 7	S 12°47'03"W	83.14'
L 8	S 12°47'03"W	16.64'
L 9	S 29°25'43"W	116.21'
L 10	S 30°42'34"W	87.77'
L 11	S 34°04'32"W	89.66'
L 12	S 34°04'52"W	26.13'
L 13	S 44°31'18"W	114.85'
L 14	S 50°43'49"W	103.41'
L 15	S 74°31'37"W	35.46'
L 16	S 64°35'56"E	207.28'
L 17	N 51°56'43"E	227.74'
L 18	N 64°24'39"W	49.79'

SCALE 1 INCH = 200 FEET  
 • 188N PIN PIN FOUND  
 ○ IRON PIN SET

SURVEY OF FOUR TRACTS  
 IN SECTION 11 AND  
 SECTION 17 T.5. R.12  
 CARTHAGE TOWNSHIP, ATHENS  
 COUNTY, OHIO  
 SURVEYED FEB. 1992



*John M. Branner*  
 JOHN M. BRANNER P.S. 6805  
 12500 N. PEACH RIDGE ROAD  
 ATHENS, OHIO 592-5778

CONFIDENTIAL