Legal Description Pre-Approval
APPROVED

All transfers are subject to Athens County Conveyance Standards

FEB 1 1 2016

Jill Thompson Athens County Auditor Description Checked for Mathematical Accuracy Athens County ENGINEER'S OFFICE

BY: Terand litellien

DATE: 2/4/16

DESCRIPTION OF A 65.04 ACRE TRACT

Situated in Section 12, T.4, R.13, Lodi Township, Athens County, Ohio and being a part of Tract One and Tract Two as described in Volume 338, Page 342 of the Official Records of Athens County and being more particularly described as follows:

Beginning at an iron pin previously set that bears North 87 degrees 08 minutes 48 seconds West, 3330.00 feet from a stone found at the North-east corner of Section 12;

Thence, along the West-line of Yount Trustee (517-371 O.R.)

S 2° 54′ 35″ W, 1692.19 feet to a point in Willow Creek Road, where an iron pin found bears

S 2° 54' 35" W, 17.36 feet;

Thence, along Willow Creek Road:

N 75° 43' 29" W, 47.66 feet;

N 64° 20' 8" W, 320.87 feet;

N 56° 51' 25" W, 243.88 feet;

N 69° 10' 28" W, 146.58 feet;

N 75° 23' 58" W, 96.99 feet;

N 82° 45' 15" W, 716.54 feet;

S 88° 51' 18" W,104.05 feet;

Thence, leaving said road and along the lines of Murrey (273-`1683 O.R.)

N 2° 24′ 57″ E, 39.50 feet to an iron pin set by a fence corner:

N 80° 46′ 37" W, 427.17 feet along a fence-line to an iron pin set;

N 3° 11' 8" E, 1239.07 feet to a stone found in the North-line of Section 12;

Thence, along the North-line of said Section 12

S 87° 03′ 24" E, 2025.01 feet to the point of beginning and containing 65.039 acres.

Subject to all easements and rights of way of record.

Iron pins set are 5/8"x 30" rebar w/ plastic I.d. cap stamped "Branner P.S. 6805

Bearings based on Grid North 1983 Ohio South Zone

The above description is based on a field survey Completed February 2016 by

John M. Branner P.S. 6805



