

S.A. ENGLAND & ASSOCIATES

Professional Land Surveying 5179 Walnut Road • P.O. Box 1770 Buckeye Lake, Ohio 43008



E-mail: www.surveyohio.com

Phone: 740-928-8680

Fax: 740-928-9565

Ohio Phone: 1-800-551-5844

Legal Description 4.373 Acres

Situated in the Township of Lodi, County of Athens, State of Ohio, and being a part of Fractional Section 25 in Section 20, Township 4N, Range 13W, of the Ohio River Survey Lands, and being more particularly described as follows;

Being a Survey of a parcel conveyed to Jerrold Sullivan, as recorded in O.R. Volume 10, Page 732, in the Athens County Deed Records, also being Auditor's Parcel No. J01-00100257-00, and further described as follows;

Commencing at a mag nail set at the intersection of the centerline of U.S. Route 33 and the South line of Fractional Section 25, being on the boundary of a parcel conveyed to John Robinson, as recorded in Deed Volume 219, Page 38, also being on the boundary of a parcel conveyed to Marjorie Gibbs, as recorded in Deed Volume 320, Page 711, and being the **PRINCIPLE PLACE OF BEGINNING**, of the **4.373 acre** parcel herein to be described: said nail bears S 84°00'00" E 1983.21 feet from a corner post found marking the Southwest corner of said Fractional Section 25;

Thence with the centerline of U.S. Route 33, the same being the boundary of said parcel conveyed to Gibbs, with the following five (5) courses and distances:

- 1) N 37°18'33" W 687.12 feet to an angle point;
- 2) N 29°15'11" W 118.40 feet to an angle point;
- 3) N 05°26'55" W 101.02 feet to an angle point;
- 4) N 06°06'04" E 320.54 feet to an angle point;
- 5) N 03°34'37" E 81.28 feet to a mag nail set;

Thence, S 83°59'09" E 74.50 feet leaving U.S. Route 33with the boundary of said parcel conveyed to Gibbs, to an iron pin set on the boundary of said parcel conveyed to Robinson, and passing over an iron pin set at 30.00 feet;

Thence with the boundary of said parcel conveyed to Robinson along the following five (5) courses and distances:

- 6) S 25°19'59" E 154.29 feet to an iron pin set;
- 7) S 09°05'42" E 430.71 feet to an iron pin set;
- 8) S 42°50'42" E 252.21 feet to an iron pin set;
- 9) S 10°20'42" E 265.49 feet to an iron pin set;
- 10) S 22°50'42" E 147.33 feet to an iron pin set on the South line of Fractional Section 25;

Thence, N 84°00'00" W40.00 feet with the South line of Fractional Section 25, the same being the boundary of said parcel conveyed to Robinson, to the PRINCIPLE PLACE OF BEGINNING.

Said parcel as surveyed contains a total of **4.373 acres**, more or less, and is subject to all legal easements, right-of-ways, zoning ordinances, and restrictions of record.

Bearings of the above description are based on the South line of Fractional Section 25 as being S 84°00'00" E, and is an assumed Meridian used to denote angles only.

All iron pins SET are 5\8" O.D. iron reinforcing bars 30" long with identification caps labeled "S.A. England #7452"

The above description is based on an actual field survey of the premises by or under the direct supervision of Scott A. England, Ohio Registered Surveyor #7452 in March of 2003.

Dated

3/19/13

Scott A. England P.S.

Ohio Registered Surveyor #7452

0979-03AT

Description checked for Mathematical Accuracy ATHENS COUNTY ENGINEER'S OFFICE

BY: (antopu



