

HAROLD D. ("DALE") WHALEY

REGISTERED SURVEYOR NO. 4986

ALBANY, OHIO 45710

Lots, Farms, Subdivisions and Construction Staking

5.00 Acre Tract
Paul Erwin

Situated in the Northeast quarter, Sec. 30, T. 4, R. 13, Lodi Twp., Athens County, Ohio and being more particularly described as follows:

Beginning at a stone at the Northeast corner of Sec. No. 30; Thence along the East line of Sec. No. 30, S. $4^{\circ} 37' 46''$ W., 429.07 feet to an iron pin;

Thence S. $56^{\circ} 21' 21''$ W., (passing an iron pin at 355.44 feet) for a total distance of 520.86 feet to an iron pin;

Thence N. $16^{\circ} 11' 10''$ W., 232.94 feet to an iron pin in the centerline of C. R. No. 75;

Thence along the centerline of C. R. No. 75, N. $52^{\circ} 08' 36''$ E., (passing a spike at 89.50 feet) for a total distance of 314.12 feet to an iron pin;

Thence along the fence line, N. $16^{\circ} 48' 30''$ W., 355.85 feet to an iron pin on the North line of Section No. 30;

Thence along the North line of Sec. No. 30, and the line between Lodi and Canaan Township, S. $84^{\circ} 00'$ E., 390.44 feet to the point of beginning, containing 5.00 acres, and being part of a 46.20 acre tract described in Vol. 268, Page 561 of the Athens County Deed Records.

Surveyed April 4, 1975 by HAROLD D. WHALEY

Harold D. Whaley
Reg. Surveyor No. 4986

Description checked for
Mathematical Accuracy
ATHENS COUNTY
ENGINEER'S OFFICE

BY: *Bruce Harter*

DATE: 4-28-75

SECT *
LODI

30

