Legal Description Pre-Approval
APPROVED

All transfers are subject to Athens County Conveyance Standards

FEB 08 2016

Jill Thompson Athens County Auditor

> JOHN M. BRANNER

ONAL SURVE

BY: STATE 2/8/16

Description Checked for Mathematical Accuracy

Athens County

DESCRIPTION OF A 77.52 ACRE TRACT

Situated in Sections 4 and 5 of T.7 North, R. 13 West, Trimble Township, Athens County, Ohio and being all of Tracts 1,2,3 as described in Volume 510, Page 261 of the Official Records of Athens County and being more particularly described as follows:

Beginning at a stone found and being the North-west corner of Sec. 34 Homer Twp., Morgan Co.,Oh.,said stone bears South 03 degrees 40 minutes 43 seconds West, 141.29 feet from a stone found at the North-east corner of Section 4, Trimble Township, Athens County, Ohio

Thence, along the East-line of Section 4 of Athens County and the West-line of Section 34 of Morgan County: S 3° 46' 08" W, 1492.86 feet to an iron pin set in the South-line of the former Federal Valley Railroad Right of Way, passing an iron pin found (stamped O.D.N.R. Div of Engr) at 821.21 feet;

Thence, along the south-line of the former Federal Valley Rail Road Right of Way and the lines of Boss, (156-299 O.R.), Athens County Commissioners (V. 31, P. 182 Comm. Journal), Davis, (508,1600 O.R.), Kovach (471-2000 O.R.)

N 10° 05' 24" W, 536.10 feet to an iron pin found, passing an iron pin found at 150.28 feet; Thence, continuing along the South-line of Federal Valley Railroad Right of way and lines of Cale (356-1940 O.R.) on a curve to the left:

Arc= 360.75 feet, Chord Bearing:N 25° 35' 04" W, 356.64 feet; Radius= 688.92 feet to an iron pin found; Thence, continuing along the South-line of Federal Valley Railroad Right of way and lines of Simons (303-2675 O.R.), Mayles (35-457 O.R.), Davis (309-751 D.R.) on a curve to the left:

Arc= 643.17 feet, Chord Bearing: N 68° 24' 05" W, 620.07 feet; Radius= 688.92 feet; to a point;

Thence, continuing along the South-line of Federal Valley Railroad Right of way and lines of Davis (309-751 D.R.)

S 4° 55' 43" E, 20.00 feet to a point;

Curve to the left:

Arc= 91.35 feet, Chord Bearing: S 81° 09' 41" W, 91.28 feet; Radius= 668.92 feet;

S 77° 15' 06" W, 72.38 feet to an iron pin set;

Thence, along the line of Central Ohio Realty (133-274 O.R.)

N 12° 44′ 54″ W, 140.00 feet to an iron pin set in the North line of the former Federal Valley Railroad Right of Way; Thence, along the former Federal Valley Railroad Right of way and lines of Metcalf (232-440 O.R.)

N 77° 15' 06" E, 78.89 feet to an iron pin set;

N 85° 35' 10" W, 639.67 feet to a stone found;

Thence, along the line of Durniat (360-59 O.R.)

N 3° 13' 51" E, 573.57 feet to a stone found;

Thence along the line of U.S.A. (190-553 O.R.)

N 3° 54' 29" E, 1349.90 feet to a stone found;

Thence, along the lines of the State of Ohio (205-619 D.R.) S 84° 52' 14" E, 1242.95 feet to an iron pin set;

Thence, along the line of the State of Ohio 1.65 acre tract (209-376 D.R.)

S 44° 59' 52" E, 545.77 feet to an iron pin found (stamped O.D.N.R. Div of Engr)

Thence, along the East line of Sections 4 and 5 of Trimble Township, Athens County and the West line of Section 35 of Homer Twp, Morgan County, Ohio

S 3° 40' 43" W, 1166.12 feet to the point of beginning and containing 77.52 acres.

Subject to all easements and rights of way of record.

Iron pins set are 5/8 inch by 30 inch long rebar w/ plastic I.D. Cap stamped Branner P.S. 6805 Basis of Bearing: Grid North- N.A.D. 83 Ohio South Zone.

The above description is based on a field survey completed January 2016 by John M. Branner P.S. 6805

